

**AMETEK**<sup>®</sup>  
CHEMICAL PRODUCTS DIVISION  
900 GREENBANK ROAD  
WILMINGTON, DE 19808  
TELEPHONE: (302) 995-0400  
FAX: (302) 995-0491  
www.ametekhaveg.com



## Material Safety Data Sheet

MSDS #15  
Date Printed 08/28/01

**Product:** Haveg 4800 Phenolic Resin

### 1. Chemical Product and Company Identification

**Trade Name** Haveg 4800 Phenolic Resin

**Synonyms** None

#### Manufacturer

AMETEK, INC., CHEMICAL PRODUCTS DIVISION  
HAVEG SITE  
900 Greenbank Road  
Wilmington, DELAWARE 19808

**24 HOUR EMERGENCY ASSISTANCE: CHEMTREC  
(800) 424-9300**  
**Phone** Product Information (302) 995-0400  
**Revision Date** October 19, 2000

#### Description

**No Hazard Rating is available for this Product**

### 2. Composition and Information on Ingredients

Ingredient(s)	CAS Number	Percent (W/W)
Phenol-Formaldehyde Resin	9003354	Proprietary Information
Phenol (Free)	108-95-2	10-12
Formaldehyde (Free)	50-00-0	1.0
Benzyl Alcohol	100-51-6	Proprietary Information

### 3. Hazard Identification

#### Emergency Overview:

Reddish-brown, low viscosity liquid with characteristic phenolic resin odor. Keep container tightly closed when not in use and do not breathe vapors unnecessarily. Do not allow this product to come in contact with strong mineral acids, such as sulfuric or hydrochloric acids, in order to prevent danger of violent exotherm occurring.

#### Effects of Overexposure:

Eye Contact: Vapors may be irritating to the eyes.

# Material Safety Data Sheet

MSDS #15

Page 2 of 6

**Product: Haveg 4800 Phenolic Resin**

Skin Contact: May be irritating to the skin, and repeated contact with the skin may cause dermatitis in sensitive individuals.

Inhalation: Vapors may be irritating to the respiratory tract.

Ingestion: Phenol (free) is highly toxic by ingestion.

Carcinogenicity Information:

## Formaldehyde

POTENTIAL CANCER HAZARD (A2)

Based on animal data and limited epidemiological evidence, NTP and IARC have listed formaldehyde as a probable human carcinogen. OSHA regulates formaldehyde as a potential human carcinogen.

May cause allergic skin reaction. Some reports suggest that formaldehyde may cause respiratory sensitization, such as asthma.

## Phenol

Can cause liver, kidney, bladder, and cardiac damage.

Pre-existing heart or circulatory disorders may be aggravated by exposure.

This material has not been listed by NTP, classified by IARC, nor regulated by OSHA as a carcinogen (A4)

Primary routes of entry:

Skin and eye contact, inhalation and ingestion.

## 4. First Aid Information

Eye Contact: Flush eyes with large amounts of water for at least 15 minutes, then seek medical attention.

Skin Contact: Remove contaminated clothing. Wash skin with mild soap and cool water.

Inhalation: Remove person from source of exposure to fresh air, then seek medical attention immediately.

Ingestion: Seek medical attention immediately.

## 5. Fire Fighting Measures

Flash Point: >210°F, ASTM Method, D 93 (PM CC)

Lower Explosive Limit (%): N.D.

Upper Explosive Limit (%): N.D.

Autoignition Temperature: N.D.

Extinguishing Media: Use water, dry chemical, or carbon dioxide.

# Material Safety Data Sheet

MSDS #15  
Page 3 of 6

**Product: Haveg 4800 Phenolic Resin**

Unusual Fire & Explosion Hazards: During a fire, free phenol and free formaldehyde may be released as well as their combustion products, and carbon monoxide and/or carbon dioxide.

Fire Fighting Instructions: Wear full fire fighting protective equipment including self-contained breathing apparatus.

## 6. Accidental Release Measures

Steps to be taken in case material is released or spilled:

1. Cover small spills with sand or other non-combustible absorbent. Do not allow spilled material to enter waterway as phenolic resin may be leached out.
2. Dispose of all waste materials in accordance with all applicable federal, state, and local environmental regulations.

## 7. Handling and Storage

### Handling:

1. Avoid skin contact. Handle with care.
2. Handle in well-ventilated area.
3. Use safety glasses with sideshields and impervious gloves when ever handling this material.

### Storage

Store material in closed containers, preferably at 35°F, to maintain maximum shelf life.

## 8. Exposure Controls and Personal Protection

### ENGINEERING CONTROLS:

#### Ventilation:

General ventilation and/or local exhaust ventilation as well as process isolation may be used to minimize employee exposure and maintain exposures below the TLV.

#### Respiratory Protection:

Use NIOSH approved full face-piece respiratory protection equipment where air contaminants exceed acceptable criteria.

#### Eye Protection:

Wear safety glasses with sideshields, or chemical splash goggles.

#### Protective Clothing:

Wear protective (impervious) gloves as required to prevent skin contact. Full body protective clothing should be worn in the event of a spill or other emergency.

#### Other Protective Equipment:

Eye wash fountain, safety shower

#### Hygienic Practices:

Use good personal hygienic practices.

# Material Safety Data Sheet

MSDS #15

Page 4 of 6

**Product: Haveg 4800 Phenolic Resin**

## EXPOSURE LIMITS:

	<u>OSHA (PEL)</u>	<u>ACGIH</u>	<u>NOTATIONS</u>
Phenolic Resin	N.E.	N.E.	
Phenol (Free)	5 ppm (skin)	5 ppm (skin)	
Formaldehyde (Free)	0.75 ppm STEL 2 ppm	(C) 0.3 ppm	A2
Benzyl Alcohol	N.E.	N.E.	

## 9. Physical and Chemical Properties

### PHYSICAL DATA:

Boiling Point: 220° F  
Melting Point: N.A.  
Solubility in Water: Slightly soluble  
Vapor Pressure: N.D.  
Vapor Density: N.D.  
Specific Gravity: 1.2  
pH: 7.1-7.9  
Color: Reddish-brown  
Odor: Characteristic phenolic resin odor  
Physical State: Low viscosity liquid

## 10. Stability and Reactivity

Chemical Stability – Product is stable at normal temperatures and storage conditions, but will polymerize at high temperatures with some evolution of heat.

Incompatibilities – Strong mineral acids such as sulfuric or hydrochloric acid, oxidizers.

Hazardous Polymerization: Hazardous polymerization will not occur under normal conditions.

Hazardous Decomposition Products: During decomposition, free phenol and free formaldehyde may be released as well as their decomposition products, and carbon monoxide and/or carbon dioxide and other unidentified organic compounds.

## 11. Toxicological Information

### Formaldehyde 50-00-0

Formaldehyde is currently listed as a suspected carcinogen by IARC and is also in the “D” list of suspected carcinogens as defined by Proposition 65 under California law.

# Material Safety Data Sheet

MSDS #15

Page 5 of 6

**Product: Haveg 4800 Phenolic Resin**

Phenol 108-95-2

Inhalation - LC 50: Mouse = 177 mg/m<sup>3</sup>

Dermal, LD50: Rabbit = 630 mg/kg

Oral, LD50: Rat = 317 mg/kg.

## 12. Ecological Information

Phenol-formaldehyde polymers have a very low rate of biodegradation. Bio-accumulation is expected to be minimal. Unreacted monomer may be leached into ground water even after normal curing has occurred.

## 13. Disposal Considerations

Dispose of all waste material including containers in accordance with applicable federal, state, and local environmental regulations.

## 14. Transportation Information

DOT Proper Shipping Name: Phenolic Resin

DOT Hazardous Class: None

DOT UN/NA Number: None

Emergency Response Guide Number: None

## 15. Regulatory Information

U.S. Federal Regulations as Follows:

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372:

Phenol                    108-95-2

Formaldehyde        50-00-0

TSCA:

The chemical substances in this product are on the TSCA Section 8 Inventory.

EXPORT NOTIFICATION:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Phenol

Formaldehyde

# Material Safety Data Sheet

MSDS #15

Page 6 of 6

**Product: Haveg 4800 Phenolic Resin**

INTERNATIONAL REGULATIONS: AS FOLLOWS:

Canadian WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

Canadian WHMIS CLASS: Not Regulated.

DSL:

The chemical substances in this product are listed on the Domestic Substances List (DSL).

## 16. Other Information

This Material Safety Data Sheet was revised in its entirety in October 2000

ABBREVIATIONS:

- 1) ACGIH – American Conference of Governmental Industrial Hygienists
- 2) OSHA – Occupational Safety and Health Administration
- 3) NIOSH – National Institute for Occupational Safety and Health
- 4) IARC – International Agency for Research on Cancer
- 5) NTP – National Toxicology Program
- 6) TLV – Threshold Limit Value
- 7) PEL – Permissible Exposure Limit
- 8) TWA – Time Weighted Average
- 9) STEL – Short Term Exposure Limit
- 10) IDLH – Immediately Dangerous to Life or Health
- 11) N.A. – Not Applicable
- 12) N.D. – Not Determined
- 13) N.E. – Not Established
- 14) DSL – Domestic Substances List

**THE ABOVE INFORMATION IS BELIEVED TO BE ACCURATE BASED ON THE MOST CURRENT DATA AVAILABLE. AMETEK MAKES NO WARRANTY, EITHER EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND ASSUMES NO LIABILITY RESULTING FROM ITS USE. USERS ARE ADVISED TO CONDUCT THEIR OWN TESTS TO DETERMINE THE SAFETY AND SUITABILITY OF EACH PRODUCT OR PRODUCT COMBINATION FOR THEIR OWN PURPOSES. AMETEK SHALL NOT BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR INCIDENTAL OR CONSEQUENTIAL DAMAGES, HOWSOEVER ARISING EVEN IF AMETEK HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.**